



Product overview

Size	Part number	Resolution	TFT Technology	C/L	Intensity (Typ.) cd/m ²	Evaluation Kit	MCU Type	Extra I/F	Touch Controller
4.3"	ETEMN043013XDHAL	480 x 272	IPS		425	EVK043013B	STM32F750	Add-On Board	ILI2511
4.3"	ETEMB043013XDHAL	480 x 272	IPS	Black	425	EVK043013B	STM32F750	Add-On Board	ILI2511
5"	ETEMN050013ADHAL	800 x 480	IPS		425	EVK05013AB	STM32F750	Add-On Board	ILI2511
5"	ETEMB050013ADHAL	800 x 480	IPS	Black	425	EVK05013AB	STM32F750	Add-On Board	ILI2511
7"	ETEMN070016XDRAM	1024 x 600	IPS	-	850		STM32H750	PoE + Add-On Board	ILI2511
7"	ETEMB070016XDRAM	1024 x 600	IPS	Black	850	EVK070016B-POE	STM32H750	PoE + Add-On Board	ILI2511
7"	ETEMW070016XDRAM	1024 x 600	IPS	White	850		STM32H750	PoE + Add-On Board	ILI2511
7"	ETEMN070019ADH6L	800 x 480	TN	-	290		STM32F750	Add-On Board	ILI2511
7"	ETEMB070019ADH6L	800 x 480	TN	Black	290	EVK070019B	STM32F750	Add-On Board	ILI2511
10.1"	ETEMN101008ADRAM	1024 x 600	IPS	-	850		STM32H750	PoE + Add-On Board	ILI2511
10.1"	ETEMB101008ADRAM	1024 x 600	IPS	Black	850	EVK101008AB-POE	STM32H750	PoE + Add-On Board	ILI2511
10.1"	ETEMN101009ADRAM	1024 x 600	IPS	-	850		STM32H750	Ethernet + Add-On Board	ILI2511
10.1"	ETEMB101009ADRAM	1024 x 600	IPS	Black	850	EVK101009AB	STM32H750	Ethernet + Add-On Board	ILI2511

Standard Interfaces: GPIO, SPI, I2C, RS232, CAN, RS485, USB-OTG
Power Supply Input range: 7-36 Volt
Add-On Board: BLE + SD-Card

Aug-22



www.smartembeddeddisplay.com